



# Safety Data Sheet

Issue Date: 01-Jan-2013

Revision Date: 16-MAR-2015

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** 830 STINGER® METALLIKA POLISH

### Other means of identification

**SDS #** SDS-830

**Product Code** 830

### Recommended use of the chemical and restrictions on use

**Recommended Use** Automotive Compound

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Stinger Chemical, LLC  
905 Live Oak Street  
Houston, Texas 77003

### Emergency Telephone Number

**Company Phone Number** Local (Houston): 713-227-1340  
Toll Free: 1-888-784-6448 (1-888-STING-IT)  
**Emergency Telephone (24 hr)** Chemtrec 1-800-424-9300 (North America) 1-703-527-3887 (International)

## 2. HAZARDS IDENTIFICATION

**Appearance** Tan lotion

**Physical State** Lotion

**Odor** Aromatic

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Germ cell mutagenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 1
Aspiration toxicity	Category 1
Flammable Liquids	Category 4

### Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed  
May be harmful in contact with skin

### Signal Word

**Danger**

### Hazard Statements

Causes skin irritation  
Causes serious eye damage  
May cause genetic defects  
Causes damage to organs  
May be fatal if swallowed and enters airways  
Combustible liquid



#### **Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Do not eat, drink or smoke when using this product  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking

#### **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a poison center or doctor/physician  
 IF ON SKIN: Wash with plenty of soap and water  
 Take off contaminated clothing and wash it before reuse  
 If skin irritation occurs: Get medical advice/attention  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do not induce vomiting  
 IN CASE OF FIRE: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### **Other Hazards**

Toxic to aquatic life with long lasting effects

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Chemical Name</b>	<b>CAS No</b>	<b>Weight-%</b>
Naphtha (petroleum), heavy alkylate	64741-65-7	15-20
Stoddard solvent	8052-41-3	12-18
Tripoli – Crystalline Silica	1317-95-9	5-15
Petroleum Distillates, Hydrotreated light	64742-47-8	1-5
Oleic acid	112-80-1	1-5
Amorphous Silica	7631-86-9	1-5
Isopropanol	67-63-0	1-5
Morpholine	110-91-8	0.2-1.2

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

## 4. FIRST-AID MEASURES

### First Aid Measures

<b>Eye Contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
<b>Skin Contact</b>	IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/ attention.
<b>Inhalation</b>	Remove to fresh air.
<b>Ingestion</b>	IF SWALLOWED: call a poison control center or physician immediately. Do not induce vomiting.

### Most important symptoms and effects

<b>Symptoms</b>	Causes skin irritation and serious eye damage. May be harmful or fatal if swallowed and enters airways.
-----------------	---

### Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Treat symptomatically.
---------------------------	------------------------

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Water. Foam. Dry chemical. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media** Not determined.

### Specific Hazards Arising from the Chemical

Combustible liquid. Can form explosive mixture at temperature at or above the flash point.

**Hazardous Combustion Products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

<b>Personal Precautions</b>	Use personal protection recommended in Section 8.
<b>Environmental Precautions</b>	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.

### Methods and material for containment and cleaning up

<b>Methods for Containment</b>	Prevent further leakage or spillage if safe to do so.
<b>Methods for Clean-Up</b>	Contain and collect with an inert absorbent and place into an appropriate container for disposal.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

#### **Advice on Safe Handling**

Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Avoid contact with skin, eyes or clothing. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe dust/fume/gas/mist/vapors/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

### Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep container tightly closed and store in a cool, dry and well-ventilated place. Store locked up. Do not allow to freeze. Store between 4°C (40°F) and 35°C (95°F). Shelf life: one year.

#### **Incompatible Materials**

None known based on information supplied.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Naphtha (petroleum), heavy alkylate 64741-65-7	100 ppm	500 ppm 2900 mg/m <sup>3</sup>	-
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
Morpholine 110-91-8	TWA: 20 ppm S*	TWA: 20 ppm TWA: 70 mg/m <sup>3</sup> (vacated) TWA: 20 ppm (vacated) TWA: 70 mg/m <sup>3</sup> (vacated) STEL: 30 ppm (vacated) STEL: 105 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 1400 ppm TWA: 20 ppm TWA: 70 mg/m <sup>3</sup> STEL: 30 ppm STEL: 105 mg/m <sup>3</sup>
Methanol 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m <sup>3</sup> (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup>
Isopropanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

**Appropriate engineering controls**

**Engineering Controls** Ensure adequate ventilation, especially in confined areas. Eyewash stations.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection** Safety goggles or safety glasses with side shields.

**Skin and Body Protection** Wear nitrile or vinyl gloves. Wear suitable protective clothing.

**Respiratory Protection** NIOSH-approved respirator or mask in the absence of adequate ventilation.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical State</b>	Lotion	<b>Odor</b>	Aromatic
<b>Appearance</b>	Tan Lotion	<b>Odor Threshold</b>	Not determined
<b>Color</b>	Tan		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	~8.0 - 9.0	
<b>Melting Point/Freezing Point</b>	Not determined	
<b>Boiling Point/Boiling Range</b>	Not determined	
<b>Flash Point</b>	40 °C / 104 °F	Tag Closed Cup
<b>Evaporation Rate</b>	Not determined	
<b>Flammability (Solid, Gas)</b>	Not determined	
<b>Upper Flammability Limits</b>	Not available	
<b>Lower Flammability Limit</b>	Not available	
<b>Vapor Pressure</b>	Not applicable	
<b>Vapor Density</b>	Not applicable	
<b>Specific Gravity</b>	0.820 - 0.860 gm/ml	
<b>Water Solubility</b>	Will mix with water	
<b>Solubility in other solvents</b>	Not determined	
<b>Partition Coefficient</b>	Not determined	
<b>Auto-ignition Temperature</b>	Not available	
<b>Decomposition Temperature</b>	Not determined	
<b>Kinematic Viscosity</b>	Not determined	
<b>Dynamic Viscosity</b>	Not determined	
<b>Explosive Properties</b>	Not determined	
<b>Oxidizing Properties</b>	Not determined	
<b>VOC Content</b>	<3% by weight	

## 10. STABILITY AND REACTIVITY

**Reactivity**

Not reactive under normal conditions.

**Chemical Stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous Polymerization** Hazardous polymerization does not occur.

**Conditions to Avoid**

Avoid high temperatures. Keep out of reach of children.

**Incompatible Materials**

None known based on information supplied.

**Hazardous Decomposition Products**

Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

<b>Product Information</b>	The information below is for repeated and prolonged contact in an occupational setting. It does not apply to normal product use
<b>Eye Contact</b>	Causes serious eye damage.
<b>Skin Contact</b>	Causes skin irritation. May be harmful in contact with skin.
<b>Inhalation</b>	Avoid breathing vapors or mists.
<b>Ingestion</b>	May be fatal if swallowed and enters airways. May be harmful if swallowed.

**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Naphtha (petroleum), heavy alkylate 64741-65-7	> 7000 mg/kg ( Rat )	> 3000 mg/kg ( Rat ) > 2000 mg/kg ( Rabbit )	> 5.04 mg/L ( Rat ) 4 h
Xylene 1330-20-7	= 4300 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit )	= 5000 ppm ( Rat ) 4 h = 47635 mg/L ( Rat ) 4 h
Petroleum Distillates, Hydrotreated light 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
Morpholine 110-91-8	= 1050 mg/kg ( Rat )	= 310 mg/kg ( Rabbit )	-
Methanol 67-56-1	= 5628 mg/kg ( Rat )	= 15800 mg/kg ( Rabbit )	= 83.2 mg/L ( Rat ) 4 h = 64000 ppm ( Rat ) 4 h
Isopropanol 67-63-0	= 4396 mg/kg ( Rat )	= 12800 mg/kg ( Rat ) = 12870 mg/kg ( Rabbit )	= 72.6 mg/L ( Rat ) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg ( Rat )	= 15354 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h

**Information on physical, chemical and toxicological effects**

<b>Symptoms</b>	Please see section 4 of this SDS for symptoms.
-----------------	--

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Germ cell mutagenicity** May cause genetic defects.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7		Group 3		
Morpholine 110-91-8		Group 3		
Isopropanol 67-63-0		Group 3		X
Ethylbenzene 100-41-4	A3	Group 2B		X

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**STOT - single exposure** Causes damage to organs.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Numerical measures of toxicity**

Not determined

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Toxic to aquatic life with long lasting effects.

**Component Information**

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Naphtha (petroleum), heavy alkylate 64741-65-7	30000: 72 h Pseudokirchneriella subcapitata mg/L EC50			2: 48 h Mysisopsis bahia mg/L LC50
Xylene 1330-20-7		13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	EC50 = 0.0084 mg/L 24 h	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Petroleum Distillates, Hydrotreated light 64742-47-8		45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static		
Morpholine 110-91-8	28: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	350: 96 h Lepomis macrochirus mg/L LC50 static 375 - 460: 96 h Oncorhynchus mykiss mg/L LC50 1000: 96 h Brachydanio rerio mg/L LC50 static	EC50 = 57.0 mg/L 30 min	100: 24 h Daphnia magna mg/L EC50
Methanol 67-56-1		28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through		
Isopropanol 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50		13299: 48 h Daphnia magna mg/L EC50
Ethylbenzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

**Persistence/Degradability**

Not determined.

**Bioaccumulation**

Not determined.

**Mobility**

Chemical Name	Partition Coefficient
Xylene 1330-20-7	3.15
Morpholine 110-91-8	-2.55
Methanol 67-56-1	-0.77
Isopropanol 67-63-0	0.05
Ethylbenzene 100-41-4	3.118



**Other Adverse Effects**

Not determined

**13. DISPOSAL CONSIDERATIONS****Waste Treatment Methods****Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**US EPA Waste Number**

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7		Included in waste stream: F039		U239
Methanol 67-56-1		Included in waste stream: F039		U154
Ethylbenzene 100-41-4		Included in waste stream: F039		

**California Hazardous Waste Status**

Chemical Name	California Hazardous Waste Status
Xylene 1330-20-7	Toxic Ignitable
Methanol 67-56-1	Toxic Ignitable
Isopropanol 67-63-0	Toxic Ignitable
Ethylbenzene 100-41-4	Toxic Ignitable

**14. TRANSPORT INFORMATION****Note**

According to 49 CFR §173.150(f)(1), this material should be reclassified as "NA1993, Combustible Liquid, N.O.S." if it is shipped in bulk.

**DOT**

Not regulated

**IATA**

Not regulated

**IMDG****Marine Pollutant**

This material may meet the definition of a marine pollutant

**15. REGULATORY INFORMATION****International Inventories****TSCA**

All ingredients are listed or exempt from listing on Chemical Substance Inventory

**Legend:***TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*

**US Federal Regulations****CERCLA**

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Methanol 67-56-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**SARA 313**

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1330-20-7	1-5	1.0
Methanol - 67-56-1	67-56-1	1-5	1.0
Isopropanol - 67-63-0	67-63-0	1-5	1.0
Ethylbenzene - 100-41-4	100-41-4	0.2-1.2	0.1

**CWA (Clean Water Act)**

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7 ( 1-5 )	100 lb			X
Ethylbenzene 100-41-4 ( 0.2-1.2 )	1000 lb	X	X	X

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Methanol - 67-56-1	Developmental
Ethylbenzene - 100-41-4	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Stoddard solvent 8052-41-3	X	X	X
Xylene 1330-20-7	X	X	X
Morpholine 110-91-8	X	X	X
Methanol 67-56-1	X	X	X
Isopropanol 67-63-0	X	X	X
Ethylbenzene 100-41-4	X	X	X

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Instability</b>	<b>Special Hazards</b>
	1	1	0	Not determined
<b><u>HMIS</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Physical Hazards</b>	<b>Personal Protection</b>
	Not determined	Not determined	Not determined	Not determined

**Issue Date:** 01-Jan-2013  
**Revision Date:** 16-MAR-2015  
**Revision Note:** New format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**